

# DL5M Floor type Low Speed Refrigerated Centrifuge



## Application

DL5M is low speed large capacity refrigerated centrifuge. It is widely used in the field of blood station, pharmaceutical factory, biochemistry, biological products and so on. It is ideal for blood bag separation, protein precipitation and cell collection.

## Features

1. Brush-less frequency motor drive, maintenance is free
2. Floor type low speed extra-large capacity refrigerated centrifuge
3. Melt housing, 304# stainless steel centrifugal chamber, safe and reliable.
4. Microprocessor control and digital display run parameters like speed, RCF and time.

## Technical Specifications

Max. RPM/RCF	Swing Out	4,000/4,730×g	
Max. Capacity	Swing Out	4x800ml	
Timer	99h~59min	RPM/RCF conversion	Yes
Noise level (dB)	≤58	Acc/Dec (sec)	There are 10 rates for your choice
Digital display	Yes	Safety lid lock system	Auto electric lid lock with Alarm
Power supply	220V 60Hz	Temperature range	-20℃~40℃
Product Dimension (W×D×Hmm)	720x540x830mm	Package Dimension (W×D×Hmm)	900x610x945mm
Weight (kg)	N.W:175kg	G.W:230kg (wooden box)	
Certificates	CE,ISO & Calibration report are available		

# Optional Rotors & Adapters for DL5M

Image	Rotor No.	Volume(ml)	Max. Speed (RPM)	Max. RCF (×g)
	30671	4x800ml (Round up)	4000	3450
				
	31377	32x15ml	4000	3200
	31377	48x10ml	4000	2880
	30690	4x18x10ml (72x10ml)	4000	3140
	30589	4x22x7/5ml (88x7/5ml)	4000	3140/2840
	31494	4x4x96well	4000	2840
	30641	12x50ml (PS: 24x50ml available)	5000	3860
	30614	6x100ml (PS: 4x100ml, 12x100ml are available)	5000	3130